2025/10/10 06:16 1/8 A

Table of Contents

4	3
ABS	3
AC or A-C	3
ACEA	3
Additive	3
Aftermarket	3
Air Cooled	4
Air Fuel Ratio	
Allen Wrench	
Alternating Current	
Alternator	
AMA	
AMPS	
Ampere-hour	
Angle- Tightening	
Ankle Biter	
Anti-Dive	
Anti-Foam Additive	
Anti-freeze	
Anti-Reversion	
Anti-Seize Compound Anti-Wear Additive	
American Petroleum Institute - (API)	
AROMATIC HYDROCARBONS	
Arvo	
Asbestos	
Ash	
ASTM	
ATF	
ATU	
Axle	
Axial Play	

http://sportsterpedia.com/ Printed on 2025/10/10 06:16

2025/10/10 06:16 3/8 A

Α

ABS

Anti-lock Braking System - "An anti-lock braking system (ABS) is a safety system that allows the wheels on a motor vehicle to maintain tractive contact with the road surface according to driver inputs while braking, preventing the wheels from locking up (ceasing rotation) and avoiding uncontrolled skidding. It is an automated system that uses the principles of threshold braking and cadence braking which were practiced by skillful drivers with previous generation braking systems. It does this at a much faster rate and with better control than a driver could manage."

AC or A-C

Air Cleaner or Air Filter - Helps to stop dirt and other objects from getting into the carburetor and thus into the engine.

ACEA

The European Automobile Manufacturers' Association (or Association des Constructeurs Européens d'Automobiles in French, hence the ACEA abbreviation) is an organization that represents the 15 most important European motor vehicle manufacturers. It's the successor of CCMC (Comité des Constructeurs du Marché Commun). According to their statement, ACEA is an advocate for the automobile industry in Europe, representing manufacturers of passenger cars, vans, trucks and buses with production sites in the EU. ²⁾

Additive

A compound mixed to the base oil in order to modify its properties or performance³⁾.

Aftermarket

Parts and companies that sell non-OEM items.

Last update: 2020/03/24 07:42

Air Cooled

An internal combustion engine cooled by a flow of air directed toward the hot parts of the engine.

Air Fuel Ratio

Allen Wrench

A hexagonal wrench (typically bent in a "L" shape) that fits in a screw head with a hexagonal hole in it. It's good for one to have both straight and bent Allen wrenches to work on a Sporty. The Allen wrenches that are built into a standard socket for use with a socket wrench are useful when trying to obtain torque specs with bolts. 4)

Alternating Current

Electric current produced by an alternator. This current requires conversion to direct current by a rectifier for charging purposes. ⁵⁾

Alternator

A motorcycle alternator converts kinetic energy (power of motion) into electrical energy to charge the battery. The alternator is made up of two parts; the stator and the flywheel. The flywheel contains permanent magnets and spins around the stator to create energy. ⁶⁾

AMA

American Motorcyclist Association - An American nonprofit organization of more than 200,000 motorcyclists that organizes numerous motorcycling activities and campaigns for motorcyclists' legal rights. Its mission statement is "to promote the motorcycling lifestyle and protect the future of motorcycling." The organization was founded in 1924 and as of October 2013 had more than 1,200 chartered clubs. The https://en.wikipedia.org/wiki/American_Motorcyclist_Association 100 chartered clubs.

AMPS

Abbreviation of Amperes. The flow rate of available electrical current as measured usually with a Digital

http://sportsterpedia.com/

2025/10/10 06:16 5/8 A

Multi-meter also known as a DMM or Volt Meter. Current = Volts ÷ Ohms.

Ampere-hour

Abbreviated (Ah). A measure of battery capacity. 8)

Angle- Tightening

A torque value as expressed in degrees and is often used after pre- torque with a conventional tightening torque value when installing heads or main bearing bolts. ⁹⁾

Ankle Biter

A small child 10)

Anti-Dive

An attachment to the lower leg of front forks to prevent the front end from diving (collapsing the lower leg into the upper leg) while hard braking. ¹¹⁾

Anti-Foam Additive

An additive to reduce the foaming of petroleum products. Can be silicone to destroy the surface bubbles or polymer to reduce the count of small internal bubbles.

Anti-freeze

Typically Ethylene Glycol mixed with water to prevent freezing and prevent rust from an engine coolant system. ¹²⁾

Anti-Reversion

* The action of exhaust creeping back up into straight pipes (dragpipes) because of no back pressure causes low-end torque to suffer in the 2000-3000 rpm range. In order to eliminate reversion, some type

Last update: 2020/03/24 07:42

of baffle, lollipop or anti-reversion cone (sometimes referred to as a 'torque cone') is needed. 13)

Anti-Seize Compound

An applied coating to fasteners to help prevent seizing under high temps, i.e. exhaust clamp bolts/ nuts.

Anti-Wear Additive

An additive that creates a thin layer with good adhesive properties in order to prevent metal-to-metal contact at high-load spots. ¹⁵⁾ Active ingredients which aim to reduce wear in mixed friction areas; a distinction is made between: ¹⁶⁾

- Mild-acting additives such as fatty acids, fatty oils (highly polar, surface-active substances), metal dithiophosphates, etc.
- High-pressure additives made of lead, sulphur, chlorine, phosphorous connections, etc.
- Solid lubricants such as graphite, molybdenum disulphide, etc. see EP additives.

American Petroleum Institute - (API)

A quality standard for 4- stroke motor oils. 17)

Ape Hangers (Apes)

High handlebars so Biker's hands are at or above their shoulder height

AROMATIC HYDROCARBONS

Hydrocarbon compounds with cyclic molecular structures. They produce viscosity temperature characteristics in lubricants and have a bad effect on resistance to oxidation. Added to fuel for sparkignition engines to prevent combustion knock. The percentages added are increasingly being limited on account of their carcinogenic effect. (18)

Arvo

Afternoon 19)

2025/10/10 06:16 7/8 A

Asbestos

A natural fibrous mineral commonly used to manufacture brake friction pads due to it's high heat resistance. Asbestos can be a health hazard if not kept contained. A fine powder residue is a by-product of the use of friction padded brake systems. This powder is an imminent health hazard if inhaled or ingested. Caution, wear your PPE while working on brakes or other asbestos containing materials.

Ash

Metallic residue/ mineral deposits formed due to the high temperature in the combustion chamber or on other engine parts that remain after lubricants have been burnt, in the form of oxides (oxide ash) or sulphate (sulphate ash after sulphuric acid has been added).²⁰⁾

ASTM

ASTM - American Society of Testing Materials - Organization that sets standards worldwide for everything from bolts to electrical wiring. Their testing methods show up on all things including lubricants and filters.

ATF

Automatic transmission fluid often used in front forks and Sporty transmissions.

ATU

Automatic Timing Unit. A mechanical device that is used for advancing the ignition timing on early engines.

Axle

A steel bolt running thru the bike frame and wheel on which the wheel rolls. AKA (Spindle)

Axial Play

A measurement of side to side movement. 22)

Last update: 2020/03/24 07:42

Go To Terminology List

```
http://en.wikipedia.org/wiki/Anti-lock_braking_system

http://www.oilspecifications.org/acea.php

http://www.oilspecifications.org/articles/lubrication-glossary.php

http://www.oilspecifications.org/articles/lubrication-glossary.php

http://www.specifications.org/articles/lubrication-glossary.php

http://www.electrosport.com/

http://www.electrosport.com/

https://en.wikipedia.org/wiki/American_Motorcyclist_Association

https://en.wikipedia.org/wiki/American_Motorcyclist_Association

https://en.wikipedia.org/wiki/American_Motorcyclist_Association

https://en.wikipedia.org/wiki/American_Motorcyclist_Association

https://www.astm.org/

http://www.motorex.com/index.cfm?oid=1195&lang=en

http://www.astm.org/
```

From:

http://sportsterpedia.com/ - Sportsterpedia

Permanent link:

http://sportsterpedia.com/doku.php/techtalk:miscres:miscres90-terms:term-a

Last update: 2020/03/24 07:42

