

SEAT COVER

Four extra seat cover clips have been added to all new Super Deluxe Buddy Seats being shipped from the factory to attach the cover more securely. If any replaceable type buddy seat covers now out in service happen to come loose from the edge of the seat shell, they can be reattached with 4 additional clips, part No. 52465-65 as described in this bulletin.

1. Remove buddy seat from motorcycle. Remove cover from edge of seat shell on both sides of saddle nose so that holes can be drilled thru metal edge of seat in locations shown in sketch.
2. Center punch and drill 4 additional 1/8 in. holes about 5/16 in. from edge as shown. Be sure seat shell is flat in area where clip is to be installed. If it is not, press or hammer the metal so it is flat. This applies to other clip locations also, since clip barb will not engage hole if clip lies on an uneven surface.
3. With seat upside down, attach additional clips on seat cover bead, being sure to line up each clip so single barb will line up and engage hole drilled in seat shell when cover is installed later.

BE SURE DOUBLE BARBS DIG INTO PLASTIC BEAD since this locks the cover to the clip.

Note: If any of the old clips are bent out of shape so they won't hold on cover or seat shell, they should also be replaced.

4. After all clips are installed on cover in correct locations, install cover clips on shell edge so single barbs snap into small holes in shell.

BE SURE SINGLE BARB ENGAGES HOLE IN SEAT SHELL since this locks the cover and clip to the seat shell. Check by trying to pull cover off near each clip.

