



# IMPORTANT!

## SPECIAL REPLACEMENT FLASHER FOR 1978 LIGHTWEIGHTS

This package contains a new rectangular LUCAS flasher and rubber strap for immediate installation on the motorcycle in this shipping crate to provide the correct turn signal flash rate. Before the motorcycle is delivered to the customer and/or operated, remove the round MITSUBA flasher and rubber strap and install the rectangular LUCAS flasher and rubber strap according to the instructions below.

Remove MITSUBA flasher (round - marked "FR-9H"), not sold for parts order.

Install LUCAS flasher (rectangular - marked "8-FL"), part number 68544-73 or 68568-76P.

Submit a warranty claim for labor only to replace round flasher following normal warranty procedure, using special Job Code 5159. When your claim is processed, you will receive 0.3 hour labor credit at your certified retail labor rate.

### INSTRUCTIONS FOR INSTALLING LUCAS FLASHER

Disconnect wires from old round flasher on motorcycle - blue wire from "L" terminal and double green wire from "X" terminal. Remove old rubber strap and flasher.

Install new rectangular flasher and rubber strap from this package by connecting blue wire to "L" terminal and double green wire to "B" terminal.

Reinstall seat, being sure to engage front ear of seat in frame crosspiece so that seat is secure. Tighten the two seat mounting bolts to 15 ft.-lbs. torque.

HARLEY-DAVIDSON MOTOR CO., INC.