



# INSTRUCTIONS

-J00096

REV. 6-1-95

Kit Numbers 41036-88, 43338-83, 43338-96, 43626-84, 43626-96, and 43628-91

## 19" CAST FRONT WHEEL

### General

This Instruction Sheet applies to the following kit numbers:

41036-88	19" Gold Wheel, 9 spoke
43338-83	19" Silver Wheel, 9 spoke
43626-84	19" Black Wheel, 9 spoke
43628-91	19" Black Wheel with Orange Stripe, 9 spoke
43338-96	19" Silver Wheel, 13 spoke
43626-96	19" Black Wheel, 13 spoke

These wheels are intended for use on 1984 and later models that come stock with 19 in. front wheels.

These wheels may also be used on 1977 XLCR, 1977 FXS-Low Rider and all 1978 - 1983 models that come stock with 19" front wheels. When installed on these vehicles an additional purchase of Screw and Spacer Kit, Part No. 43406-83 will be necessary.

### Installation

1. Refer to applicable Service Manual for detailed wheel removal and installation procedures.
2. These wheels are assembled with a left wheel bearing spacer that fits 1984 to present vehicles. If used on 1984 and later vehicles, proceed to Step 3. If used on 1977 - 1983 vehicles, proceed to Step 5.

3. **1984 and later models only.** To attach brake disc to wheels, use the appropriate new screws supplied with the wheel.

#### NOTE

*If the original screws were pan head style, use the pan head screws supplied with the new wheel. If the original screws were flat head style, use the flat head screws supplied with the new wheel.*

Refer to the appropriate Service Manual for proper torque specifications.

4. Install wheel as detailed in Service Manual.
5. **1977 - 1983 models only.** When installing wheels on 1977 - 1983 models listed in General Section of this instruction sheet, the purchase of Screw and Spacer Kit, Part No. 43406-83 is required. It is important to follow the instructions included with the Screw and Spacer Kit for proper wheel installation.

#### ⚠WARNING

**On 1977 - 1983 models, if the original tire is still in use and it has a tire designation ending with the letter "T" (ie. MM90-19T), do not use the tire on this wheel. These tires will not fit properly and could malfunction during normal operation resulting in personal injury and/or property damage. See your authorized Harley-Davidson dealer for correct tire selection.**