



INSTRUCTIONS

-J01119

REV. 8-1-88

Kit Numbers 40983-86, 41015-86

WHEEL KIT

General

These wheel kits are furnished with two sets of sprocket bolts. The purpose of this Instruction Sheet is to specify the correct bolts for each application. Refer to the GENERAL Instruction Sheet, also included, for detailed procedures to mount to tire and wheel onto vehicle.

Installation

If wheel is to be used on **XL model vehicles** attach sprocket to wheel with 7/16-14 x 1-1/2 in. bolts. Torque to 50-55 ft-lbs (68-75 Nm).

If wheel is to be used on **FXR model vehicles** attach sprocket to wheel with 7/16-14 x 1-3/4 in. bolts and 7/16 in. flat washers. Torque to 65-70 ft-lbs (88-95 Nm).



INSTRUCTIONS

-J01119

REV. 8-1-88

Kit Numbers 40983-86, 41015-86

WHEEL KIT

General

These wheel kits are furnished with two sets of sprocket bolts. The purpose of this Instruction Sheet is to specify the correct bolts for each application. Refer to the GENERAL Instruction Sheet, also included, for detailed procedures to mount to tire and wheel onto vehicle.

Installation

If wheel is to be used on **XL model vehicles** attach sprocket to wheel with 7/16-14 x 1-1/2 in. bolts. Torque to 50-55 ft-lbs (68-75 Nm).

If wheel is to be used on **FXR model vehicles** attach sprocket to wheel with 7/16-14 x 1-3/4 in. bolts and 7/16 in. flat washers. Torque to 65-70 ft-lbs (88-95 Nm).