



INSTRUCTIONS

-J01123

REV. 11-1-91

Kit Number 44135-74A

BRAKE PAD SET

General

This Brake Pad Set contains sintered metallic pads. It is designed for installation on the following model vehicles only, provided that each original hard- chrome- plated brake disc has been replaced with Disc and Spacer Kit (Part No. 41806-72B or 41806-92), or with Disc (Part No. 41813-79 or 41813-92) and Spacer (Part No. 41814-76A):

- 1972 to 1975 FL (front and rear discs)
- 1973 FX (front disc); 1973 to 1975 FX (rear disc)
- 1973 XL (front disc)

A Service Manual for your model motorcycle is available from your Harley- Davidson dealer.

CAUTION

Do not install this Brake Pad Set (Part No. 44135-74A) on vehicles equipped with the original hard- chrome- plated brake disc(s); the metallic pads will cause severe scratching of the discs(s). Refer to chart below to determine the compatible disc and pad combinations. If this Brake Pad Set is to be installed on models with the original hard- chrome- plated brake disc(s), the original disc(s) **MUST** first be replaced with compatible Disc(s) and Spacer(s) as listed in the chart below.

Installation

1. Refer to appropriate Service Manual for proper installation procedures.

BRAKE DISC		PAD INFORMATION
Part No.	Identification	
41806-72, Disc (original equipment on models specified above) This disc is now OBSOLETE.	Center offset, chrome-plated and marked "MIN. THICKNESS 0.188"	Designed for use with Organic Pads, Part No. 44131-72. These pads are now OBSOLETE.
41806-72B, Disc & Spacer Kit (Kit includes spacer P/N 41814-76A)	P/N 41813-79 stamped on Disc and marked "MIN. THICKNESS 0.205"	Designed for use with Metallic Pads, Part No. 44135-74A.
41318-79, Disc (used with spacer P/N 41814-76A)	P/N 41813-79 stamped on Disc and marked "MIN. THICKNESS 0.205"	Compatible for use with Metallic Pads, Part No. 44135-74A.
41806-92, Disc & Spacer Kit (Kit includes spacer P/N 41814-76A)	P/N 41813-79 stamped on Disc and marked "MIN. THICKNESS 0.205"	Compatible for use with Metallic Pads, Part No. 44135-74A.
41813-92, Disc (used with spacer P/N 41814-76A)	P/N 41813-79 stamped on Disc and marked "MIN. THICKNESS 0.205"	Compatible for use with Metallic Pads, Part No. 44135-74A.