-J04670 2011-10-19

REAPER FRONT AND REAR FLOATING ROTOR KITS

GENERAL

Kit Numbers

44411-09, 44421-09, 41500066

Models

For model fitment information, see the P&A Retail Catalog or the Parts and Accessories section of www.harley-davidson.com (English only).

Additional Parts Required

Installation of rear disc kit (44421-09 & 41500066) on FXSTD 17-inch wheels requires separate purchase of brake rotor hub plate (43837-00).

WARNING

Rider and passenger safety depend upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, have a Harley-Davidson dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00333b)

NOTE

This instruction sheet references service manual information. A service manual for your model motorcycle is required for this installation and is available from a Harley-Davidson Dealer.

Kit Contents

See Figure 1 and Table 1.

INSTALLATION

NOTE

The floating disc screw holes are countersunk to accept the retaining screw heads. Be sure to install the screws properly.

- See the service manual for rotor removal, assembly and disassembly procedures.
- Assemble the brake disc pads as described in the service manual.
- 3. See Figure 1. Install the new screws (1).
- 4. Tighten rear disc screws to 40.7-61 N·m (30-45 ft-lbs).

NOTE

Avoid hard stops for the first 100 miles. Hard stops during the wear-in period will gall discs.

5. Tighten front disc screws to 21.6–32.5 N·m (16–24 ft-lbs).

SERVICE PARTS




Figure 1. Service Parts: Reaper Floating Rotor Kits

Table 1. Service Parts: Reaper Front and Rear Floating Rotor Kits

Item	Description (Quantity)	Part Number
Kit 44411-09 Front Floating Rotor Kit		
1	Screw, front disc (5)	3655A
		Not Sold Separately
Kit 44421-09 & 41500066 Rear Floating Rotor Kit		
1	Screw, rear disc (5)	43567-92
2	Brake disc, rear	Not Sold Separately